

# 184 U

## Dump Body Drop Side

**STANDARD:** LENGTH . . . . . 8', 9', 10' and 11'  
WIDTH . . . . . 84 inches inside  
CAPACITY . . . . . 2-3 cubic yards

Headboard and tailgate is 6 inches higher than sides.  
All bodies are shipped powder coated black prime.

### SPECIFICATIONS:

#### Sides:

10-gauge high tensile steel A572 with boxed top rail and full-length sloping rear corner posts. Fully welded full depth rear corner posts

#### Floor:

10-gauge high tensile steel A572

#### Head:

Full width inverted V-horizontal head brace. 10 gauge steel construction, 16" cab protector.

#### Tailgate Hardware:

Heavy duty cast quick release top hardware and cast overshoot lower hardware with manual release handle.

#### Understructure:

5" structural channel longitudinals. 3" structural channel crossmembers. Understructure gusseted and welded to body.

#### Options:

- 24" cab protector
- 36" cab protector
- 3/16" one piece floor
- Quick release latch
- Tarp system

The body in the photographs on the front and above are equipped with an optional tarp system, quick release upper tailgate hardware and customer installed rear spreader mount brackets.



Shown is one of the sides in the down position. The side easily unlatches with a single handle and folds down lower than the body floor for greater access to the interior.

### Quality Control Assures Top Quality



Shown is the standard F-latch upper hardware with keeper chain.

Godwin Manufacturing Company, Inc.

Highway 421 South - P.O. Box 1147 - Dunn, North Carolina 28335

(910) 892-0141 Fax: (910) 892-7402